


No. 6-16²
Art.-Nr. 20090

No. 6-16²
Part No. 20090



Arbeitsbereich:

Ergonomische, automatische Abisolierzange für massive und flexible Leiter mit PVC Außenisolierung von 6 - 16 mm² (AWG 10 - 6). Auch zum Entmanteln von PVC-Flex 3x0,75mm² oder Solarkabel mit verbundener Doppelisolation (z. B. Solarflex®, Energyflex®).

Keine Einstellung auf Kabelquerschnitt notwendig. Abisolieren jeder beliebigen Länge möglich auf Grund der Kabeldurchführung im Griff. Längenskala aufgedruckt, die Klingenkassette ist austauschbar.

Ersatzteile

EM-Set No. 6-16² - Art.-Nr.: 29090

Ersatzmesser-Set für die Abisolierzange No. 6-16²

Warnhinweis

Nicht für Arbeiten an oder in der Nähe unter elektrischer Spannung stehender Teile.

Working Range:

Automatic wire stripper which is suitable for standard round wires with cross sections from 6 to 16mm² (AWG 10-6). This tool will remove the PVC outer cable insulation. Also suitable for stripping the sheathing of PVC-Flex 3x0,75mm² and solar cables with jointed cable sheathings (e.g. Solarflex®, Energyflex®).

Stripping of any length possible due to open frame construction of handles. Length scale printed on handle. The blade cassette is replaceable.

Spare parts

EM-Set No. 6-16² - Part No.: 29075

Spare blade set for wire stripper No. 6-16²

Warning

Never use tool on or near live electrical circuits.



Datenblatt / Datasheet

Art.-Nr. / Part No.: 20090

EAN: 4011391200906

HSCode: 8203 2000

Ursprungsland: BR Deutschland

Country of Origin: Germany

Nettogewicht: 152 g

Net weight: 5.36 oz

Maße:	A	172 mm	6.772"
Dimensions:	B	98 mm	3.858"
	C	30 mm	1.181"
	MA	30 mm	1.181"
	MB	13 mm	0.512"


Material

Gehäuse: Glasfaserverstärktes Polyamid (PA)
 Thermoelastisches Elastomer (TPE)

Body: fibreglass reinforced polyamide (PA)
 thermoplastic elastomer (TPE)

Klinge: Spezialstahl, gehärtet

Blade: special steel, hardened and tempered



Video Scan



4 011391 200906